

8800 SERIES FLORIDA BUILDING COMMISSION (FBC) PRODUCT APPROVAL CHART (NON-HVHZ)

Style	Design Pressure	Maximum Size		Glass Strength	Reinforcement	Air	Water	FBC Approval
Vinyl Double Hung Window	DP65	54.000	X 76.000	DST-LAMI (SGP090)	A8	0.05 cfm/ft2	9.75 psf	FL15819.2
	DP60	48.000	X 72.000	DS-LAMI (PVB090)	A8	0.08 cfm/ft2	9.75 psf	
	DP55	54.000	X 76.000	DST-LAMI (PVB090)	A8	0.06 cfm/ft2	9.75 psf	
	DP50	54.000	X 84.000	DS-LAMI (PVB090)	A8	0.07 cfm/ft2	7.50 psf	
Vinyl Horizontal Sliding Window (XX)	DP65	74.000	X 63.000	DST-LAMI (SGP090)	A8	0.02 cfm/ft2	9.75 psf	FL16092.4
	DP55	74.000	X 62.000	DS-LAMI (PVB090)	A8	0.01 cfm/ft2	9.75 psf	
	DP50	74.000	X 63.000	DST-LAMI (PVB090)	A8	0.02 cfm/ft2	9.75 psf	
Vinyl Horizontal Sliding Window (XOX-424)	DP60	112.000	X 63.000	DST-LAMI (SGP090)	A8	0.01 cfm/ft2	9.75 psf	FL16092.5
	DP50	112.000	X 63.000	DST-LAMI (PVB090)	A8	0.02 cfm/ft2	9.75 psf	
	DP45	110.000	X 62.000	DS-LAMI (PVB090)	A8	0.04 cfm/ft2	9.75 psf	
Vinyl Horizontal Sliding Window (XOX-333)	DP60	86.000	X 63.000	DST-LAMI (SGP090)	A8	0.01 cfm/ft2	9.75 psf	FL16092.5
	DP55	110.000	X 62.000	DS-LAMI (PVB090)	A8	0.01 cfm/ft2	9.75 psf	FL16092.6
	DP50	86.000	X 63.000	DST-LAMI (PVB090)	A8	0.02 cfm/ft2	9.75 psf	FL16092.5
Vinyl Fixed Window (Picture)	DP65	64.000	X 64.000	LAMI-DST (SGP090)	NO	<0.01 cfm/ft2	12.00 psf	FL15816.2
		37.000	X 84.000	LAMI-DST (SGP090)	NO	<0.01 cfm/ft2	9.75 psf	
		76.000	X 63.000	LAMI-3ST (SGP090)	NO	<0.01 cfm/ft2	15.00 psf	
		72.000	X 72.000	LAMI-3ST (SGP090)	NO	<0.01 cfm/ft2	9.75 psf	
	DP50	48.000	X 60.000	LAMI-DS (PVB090)	NO	<0.01 cfm/ft2	7.50 psf	
		37.000	X 84.000	LAMI-DS (PVB090)	NO	0.04 cfm/ft2	7.50 psf	
		64.000	X 64.000	LAMI-3S (PVB090)	NO	<0.01 cfm/ft2	7.50 psf	
		72.000	X 72.000	LAMI-3S (SGP090)	NO	<0.01 cfm/ft2	12.00 psf	
Vinyl Out-Swing Casement Window	DP65	36.000	X 72.000	LAMI-DST (SGP090)	NO	<0.01 cfm/ft2	15.00 psf	FL15817.2
	DP55	36.000	X 72.000	LAMI-DST (PVB090)	NO	<0.01 cfm/ft2	15.00 psf	
	DP50	36.000	X 72.000	LAMI-DS (PVB090)	NO	<0.01 cfm/ft2	7.50 psf	
Vinyl Awning Window	DP55	53.000	X 32.000	LAMI-DST (PVB090)	NO	<0.01 cfm/ft2	15.00 psf	FL15818.2
	DP50	53.000	X 32.000	LAMI-DS (PVB090)	NO	<0.01 cfm/ft2	9.75 psf	
Vinyl Sliding Glass Door (XO)	DP50	94.500	X 94.500	DST-LAMI (PVB090)	E4	0.07 cfm/ft2	7.50 psf	FL16216.1
		96.000	X 96.000	DST-LAMI (SGP090)	E4	0.02 cfm/ft2	9.75 psf	
Vinyl Sliding Glass Door (XOX)	DP50	141.000	X 96.000	DST-LAMI (PVB090)	E4	0.07 cfm/ft2	7.50 psf	FL16216.2

Additional Notes

- 1) All structural testing performed in accordance with Test Standard AAMA/WDMA/CSA 101/I.S.2/A440
- 2) All impact testing performed in accordance with Test Standards ASTM E 1886 & ASTM E 1996 (Missile "D" Windzone 4)
- 3) All product performance testing was performed by an "Approved Agency", as required in Section 1703 of the International Building Code (IBC)
- 4) "Maximum Size" listed can not be exceed in order to maintain corresponding product performance and product certification

Additional Notes "Continued on Page 2"

8800 SERIES FLORIDA BUILDING COMMISSION (FBC) PRODUCT APPROVAL CHART (NON-HVHZ)

Additional Notes "Continued"

- 5) "Glass Strength" listed reflects the minimum glass strength to be utilized in order to maintain corresponding product performance and product certification
- 6) "Reinforcement" listed reflects the minimum reinforcement configuration to be utilized in order to maintain corresponding product performance and product certification
- 7) "FBC Approval" listed is the product approval number assigned to Wincore by the Florida Building Commission (FBC), for use in Non-HVHZ designated areas

